

Product Code: DPMMSV10 (Matte)

10oz. Scrim Vinyl Banner Eco/Solvent, UV-IR Curable & Screen Inks

The Nazdar SourceOne's ImageStar 10oz. Scrim Vinyl Banner material is a high quality coated material for eco-solvent, solvent, UV-IR curable and screen ink sets. This 10oz./ 11-mil product provides outstanding image quality with a warm white vs. blue white surface color. Our 10oz scrim digital media product is ideal for general purpose banners & posters and can be used for indoor & outdoor applications and provides one year outdoor durability without lamination. Special Order only, available in 36", 54" & 61" X 750 ft. rolls

Property	Specifications												
Support Cloth	Polyester												
Yarn	250D x 500D												
Threads	9 x 9												
Total Weight	330 g/m2 or 10 oz/yd2												
Tensile Strength	Weft 1,400 N/5cm, Warp 1,400 N/5cm												
Tear Strength	Weft 200 N, Warp 200 N												
Peel Strength	40 N/5cm												
Temperature Resistance	-20 to 70°C or -22 to 158°F Recommended RH% for Printing: 45% to 70%												
Fungus Resistant	Yes												
Fire Resistance	CA 701, ASTM E84, Class B												
White Point	Matte 77												
Gloss Level	Matte 8-15												
Light Fastness	The fading time of ink jet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Please consult with your ink manufacture for light fastness data.												
Finishing/Post Process	Pressure sensitive vinyl laminates can be applied to increase the fade and abrasion resistance of the image. Polyester or other base material laminates are not recommended. Before applying the laminate, allow the image to dry for 12- 24 hours. Residual solvent trapped beneath a laminate as a result of insufficient dry time can cause color shifts and de-lamination.												
Grommeting	Grommets should be placed in the hemline along the length of the banner so that the grommet is through two layers. Corner grommets should be placed where the length and width hems cross so that the grommet is through four layers. A reinforced corner is also recommended to increase durability.												
Tape & Stitched Hem	Banner tape can be used and is preferred to sewing. If sewing, a double-stitched hem is recommended with a maximum of five stitches per inch. Banner tapes at least 4-mils thick perform the best.												
Item Numbers & Sizes	<table border="0"> <tr> <td>DPMMSV103650</td> <td>36" X 750'</td> </tr> <tr> <td>DPMMSV103831</td> <td>38" X 131'</td> </tr> <tr> <td>DPMMSV105431</td> <td>54" X 131'</td> </tr> <tr> <td>DPMMSV105450</td> <td>54" X 750'</td> </tr> <tr> <td>DPMMSV106131</td> <td>61" X 131'</td> </tr> <tr> <td>DPMMSV106150</td> <td>61" X 750'</td> </tr> </table>	DPMMSV103650	36" X 750'	DPMMSV103831	38" X 131'	DPMMSV105431	54" X 131'	DPMMSV105450	54" X 750'	DPMMSV106131	61" X 131'	DPMMSV106150	61" X 750'
DPMMSV103650	36" X 750'												
DPMMSV103831	38" X 131'												
DPMMSV105431	54" X 131'												
DPMMSV105450	54" X 750'												
DPMMSV106131	61" X 131'												
DPMMSV106150	61" X 750'												

Product Performance & Suitability: All of the descriptive information and recommendations for the use of ImageStar Media should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers of the ImageStar Media shall independently determine the suitability of the material for the purpose for which it is purchased. Sellers only obligation shall be to replace such quantity of the product proved to be defective. The seller shall not be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including ink, labor and loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller.