

Nazdar® 910 Series Digital Imaging Inks are designed for use in HP 9000 & HP10000 Designjet™ Printers. Conveniently packaged in 1 liter fully compatible cartridges along with 1 liter bottles, they provide a great value, high performance alternative to the OEM.

Primary Features & Substrates

Features

- Color matched to HP790 inks*, avoiding the need to profile in most situation.
- Fully compatible, no-flush formulation.
- Long term exterior performance with proven resistance to the effects of UV degradation and fading.
- High impact, high intensity colors equivalent to the original OEM HP790 ink set.
- Consistent color density values.
- Excellent adhesion and flexibility on most digital inkjet media.

Substrates

- Self-Adhesive, flexible and pressure sensitive vinyl.
- Banner Material
- Blue back paper
- Backed mesh

Ink Handling

All personnel mixing and handling these products must wear gloves and eye protection. Clean up all spills immediately. If ink does come in contact with skin, wipe ink off with a clean, dry cloth (do not use solvent or flush solution). Wash the affected area with soap and water. Consult the Nazdar® 910 Series Material Safety Data Sheet for further instructions and warnings.

Ink Changeover

When changing from HP 790 original ink cartridges to Nazdar 910 series cartridges operators should remove the empty OEM ink cartridge and replace with a Lyson ink cartridge and continue printing. This can be carried out either one color at a time or all colors together.

No ink fills are required.

For conversions from non OEM inks or bulk feed systems please consult www.nazdar.com.

Clean Up

Use item number LWS910FF Flush Solution for the most effective cleanup of ink spills and cleaning of jet assemblies. Avoid contact with skin. Wear approved safety glasses and appropriate gloves when using Maintenance Solution. Consult MSDS for further safety precautions.

Storage/Shelf Life

Storage and transportation of ink and cleaning solutions should be carried out between 5° - 25°C (41° - 77°F). Ink and cleaning solutions should always be kept away from heat, sparks, and flames. If stored or transported at a different temperature, the ink should be allowed to reach room temperature before calibration or printing. This may have an adverse effect on performance and will affect any warranties given by Nazdar®.

Recommended shelf life of this product is 15 months from the date of manufacture when stored under preferred conditions.

Ink Performance

Outdoor Durability

Nazdar® 910 Series Inks are designed for maximum outdoor resistance to color fade and chemical attack caused by the combined effects of UV degradation and environmental pollution.

Each color is formulated with durable long-term outdoor pigments. When Nazdar® 910 Series Inks are used with proper color management, color variance of the original print density will be minimal over a period of 24 months for vertical outdoor exposure.

To ensure the color properties of Nazdar® 910 Series inks do not change during outdoor exposure, it is important to use proven substrates (flexible vinyls and pressure sensitive vinyls) that do not "yellow" or vary from their original white cast when exposed outdoors. All Nazdar® 910 Series Inks are formulated for maximum adhesion to an extensive range of unsupported and pressure sensitive vinyls. Always pretest for acceptable adhesion prior to production.

Digital Solvent Inkjet

Nazdar 910 Series Solvent Inkjet Ink



v 10 EN

Ref: v10 EN

Environmental Operating Parameters

Temperature:

- 66 ° F – 80 ° F [19 ° C – 27 ° C]

Humidity:

- Optimum: 40% - 60% (non-condensing)
- Operational: 30% - 70% (non-condensing)

Nazdar Quality Statement

Nazdar® stands behind the quality of this product. Nazdar® cannot, however, guarantee the finished results because Nazdar® exercises no control over individual operating and production procedures. While technical information and advice on the use of this product is provided in good faith, the user bears sole responsibility for selecting the appropriate product for their end use requirements. Users are also responsible for testing to determine that our product will perform as expected during the printed item's entire life cycle from printing, post print processing, and shipment to end use. This product has been specially formulated for digital printing, and it has not been tested by any other method. Any liability associated with the use of this product is limited to the value of the product purchased from Nazdar®.

Based on information from our raw material suppliers, these products are formulated to contain less than 0.06% lead. If exact heavy metal content is required, independent lab analysis is recommended.

Validated Equipment

Nazdar® 910 Series Inks are designed for use in the following printer platforms:

- Cartridges compatible with HP 9000 & HP10000 Designjet™ using HP 790 original ink.

Manufacturers Product Offering

All colors listed below are available in 1 liter cartridges. Flushing solution is available in 500ml cartridges and 1 liter containers. Maintenance fluid is available in 500ml liter cartridges. Contact your Nazdar distributor for product availability and offering.

Inks

Item Number	Color
LWS910CY	Cyan
LWS910MA	Magenta
LWS910YE	Yellow
LWS910KK	Black
LWS910CL	Light Cyan
LWS910ML	Light Magenta

Flush

Item Number	Color
LWS910MF	910 Series Maintenance Fluid
LWS910FF	910 Series Cleaning Fluid

Nazdar Ink Technologies Offices Worldwide

Nazdar Ink Technologies -World Headquarters

8501 Hedge Lane Terrace
Shawnee, KS 66227-3290 USA

Toll Free US: 866-340-3579

Tel: +1 913-422-1888

Fax: +1 913-422-2296

E-mail: NazdarOrders@nazdar.com

Technical Support E-mail: InkAnswers@Nazdar.com

Nazdar Limited – EMEA

Battersea Road, Heaton Mersey
Stockport, England SK4 3EE

Tel: + 44 (0)-161-442-2111

Fax: + 44 (0)-161-442-2001

EMEA Technical Service E-mail:

technicalservicesuk@nazdar.com

Nazdar – Asia Pacific

11, Changi North Street 1 #03-03/04
Singapore 498823

Tel: +65-6385 4611

E-mail: aspac@nazdar.com

Digital Solvent Inkjet