

NWC20 EZR Cleaner cleans Water-Based and UV Inks from surfaces such as photopolymer plates and aniloxes.

APPLICATION AND USE

User Information

NWC20 EZR Cleaner may be used as a spray and wipe. After scrubbing surface with EZR Cleaner, rinse or wipe away using water or a water miscible solvent such as Isopropyl Alcohol. Wear appropriate PPE and consult SDS before use. NWC20 is a "0" for Fire.

FEATURES AND BENEFITS

- Will not damage rubber or photopolymer plates.
- Low odor and non-flammable product.
- Cleans conventional and most UV and water based flexographic inks.

Materials may be immersed in EZR Cleaner for 1-30 minute period. Note-when cleaning Aluminum or Aluminum Alloy materials, immerse for 1-5 minutes only.

If sonic cleaning equipment is being used for aniloxes and metering rolls, it may be necessary for these parts to remain in the cleaner for a longer time. Set tank temperature to less than 140°F.

NWC20 EZR Cleaner is to be used at 100% strength.

STORAGE AND HANDLING

Safety glasses and gloves are suggested in areas where product may be splashed. If product contacts skin, wipe off with a clean, dry cloth (do not use solvent). Wash the affected area with soap and water. Consult Material Safety Data Sheet for further instructions and warnings. Protect from freezing

SHELF LIFE

12 months (Unopened containers all sizes)
Please consult Shelf Stability from Date of Manufacture at [Shelf Life Chart](#) for other for other container sizes, fluorescents & metallics. Protect from Freezing

PRODUCT OFFERING

Cleaners	Stock No.	Weight
EZR Clean 1 Gallon Jug	NWC20N8	8lb
EZR Clean 5 Gallon Bucket	NWC20B3	40lb
EZR Clean 55 Gallon Drum	NWC20D7	484lb

Nazdar® stands behind the quality of this product. Nazdar® cannot, however, guarantee the finished results because Nazdar® exercises no control over individual operating conditions and production procedures. While technical information and advice on the use of this product is provided in good faith, the User bears sole responsibility for selecting the appropriate product for their end-use requirements. Users are also responsible for testing to determine that our product will perform as expected during the printed item's entire life-cycle from printing, post-print processing, and shipment to end-use. Any liability associated with the use of this product is limited to the value of the product purchased from Nazdar®.

Nazdar - World Headquarters
8501 Hedge Lane Terrace, Shawnee, KS 66227-3290 USA
Toll Free US:+1 866.340.3579
Tel: +1 913 422-2255
E-mail: custserv@nazdar.com
Technical Service Email: InkAnswers@Nazdar.com

Nazdar Limited - England
Barton Road, Heaton Mersey, Stockport, England SK4 3EG
Tel: +44 161 442 2111
Technical Service Email: technicalservicesuk@nazdar.com