

**LWU7040NC Adhesion Promoter has been formulated as a primer to improve adhesion of Nazdar UV curable digital inks to substrates such as polypropylene and acrylic. Previously known as Print Bond v2, only available in European market.**

## Substrates

Acrylics (PMMA)  
Treated fluted/corrugated polypropylene (PP)  
Dibond® (and other composite enameled aluminum panels)  
Clear polycarbonate (PC)

*Substrate recommendations are based on commonly available materials intended for the ink's specific market when the inks are processed according to this technical data. While technical information and advice on the use of this product is provided in good faith, the User bears sole responsibility for selecting the appropriate product for their end-use requirements. Reference the 'Quality Statement' at the end of this document.*

## Applications

Primer was designed to be used as a wipe on primer. Shake container to mix contents prior to application. Dip a clean, lint free, dry towel into a container of primer and wipe onto the substrate to be printed. Cover the entire substrate with primer making sure to get a uniform deposit across the substrate.

## Processing

- Allow the primer to dry thoroughly. (Approx. 10 minutes depending on humidity levels).
- Print the newly primed surface as soon as possible. The primed surface may be printable for up to 24 hours after application of the primer, possibly less in very humid environments.
- UV curable inks should be printed onto the thoroughly dried primer.
- For best adhesion, allow the printed surface to post-cure for 24 hours at room temperature.

## General Information

### Handling

Refer to the SDS for recommendations on handling.

Wear gloves and barrier cream to prevent direct skin contact. Safety glasses are suggested in areas where ink may be splashed. If product does come in contact with skin, wipe ink off with a clean, dry cloth (do not use solvent or reducer). Wash the affected area with soap and water.

### Environmental Operations Parameters

Temperature:

- 18° C – 27° C [65° F – 80° F]

Humidity:

- Optimum: 40% - 60% (non-condensing)
- Operational: 30% - 70% (non-condensing)

### Storage / Shelf Life

Store product at 18° - 32° C (65° - 90° F). Chemistries should always be kept away from heat, sparks, and flames. The shelf life of this product is 24 months from the date of manufacture when stored under prescribed conditions.

## Standard Color Range

Based on information from our raw material suppliers, these ink products are formulated to contain less than 0.06% lead. If exact heavy metal content is required, independent lab analysis is recommended.

## Packaging / Availability

Contact your Nazdar distributor for product availability and offering.

### Packaging / Availability Product Specific

Adhesion promoters are available in 1-liter containers.

# Nazdar UV Inkjet Adhesion Promoter - 7040



Item Type	Item Number	Item (or Color) Description
Adhesion Promoter	LWU7040NC	LWU7040NC Adhesion Promoter

## Nazdar Quality Statement

*Nazdar® stands behind the quality of this product. Nazdar® cannot, however, guarantee the finished results because Nazdar® exercises no control over individual operating conditions and production procedures. While technical information and advice on the use of this product is provided in good faith, the User bears sole responsibility for selecting the appropriate product for their end-use requirements. Users are also responsible for testing to determine that our product will perform as expected during the printed item's entire life-cycle from printing, post-print processing, and shipment to end-use. This product has been specially formulated for screen printing, and it has not been tested for application by any other method. Any liability associated with the use of this product is limited to the value of the product purchased from Nazdar®.*

## Nazdar Ink Technologies Offices

Nazdar Ink Technologies - World Headquarters  
 8501 Hedge Lane Terrace  
 Shawnee, KS 66227-3290 USA  
 Toll Free US: 866-340-3579  
 Tel: +1 913-422-2255  
 Fax: +1 913-422-2296  
 Customer Service E-mail: [NazdarOrders@nazdar.com](mailto:NazdarOrders@nazdar.com)  
 Technical Support E-mail: [TechSupport@Nazdar.com](mailto:TechSupport@Nazdar.com)

Nazdar Limited – EMEA  
 Battersea Road, Heaton Mersey  
 Stockport, England SK4 3EA  
 Tel: + 44 (0)-161-442-2111  
 Fax: + 44 (0)-161-442-2001  
 EMEA Customer Service E-mail: [infoUK@nazdar.com](mailto:infoUK@nazdar.com)  
 EMEA Technical Service E-mail: [technicalservicesUK@nazdar.com](mailto:technicalservicesUK@nazdar.com)

Nazdar – Asia Pacific  
 11 Changi North Street 1  
 #03-03/04  
 Singapore 498823  
 Tel: +65 6385 4611  
 E-mail: [aspac@nazdar.com](mailto:aspac@nazdar.com)