

[View Translatable Version](#)**Description**

OP61002 UV LED Gloss Imprintable Varnish is used to provide a stampable/imprintable coating over many water based, solvent based, and UV curable inks. OP61002 exhibits high gloss and is specifically formulated for Tag and Label printing. The overprint clear has excellent rheology characteristics making it ideal for most printing equipment, and product applications.

This coating has been specifically formulated for use with 16W/cm² UV LED curing lamps, which have an output wavelength of 395nm.

Substrates

Pressure sensitive vinyl's, top coated and print treated polyester, BOPP films, polyethylene, polystyrene and some paper and board.

Properties

Shelf Life 6 months (Unopened containers)
Benzophenone (BP) This product is formulated with Benzophenone.

Application Suggestions

An anilox with a BCM range of 5.0 - 10.0 is suggested for flexo applications, with a reverse angle doctor blade.

This product is formulated to be press ready and can be printed over Nazdar[®] Rotary Screen, UV Flexo and Water Base Flexo inks.

Performance Verification

After press/job set up is complete, inspect a portion of the printed web for all applicable and specified properties. These properties include but are not limited to: cure, adhesion, mar and rub resistance, product resistance, gloss, and coefficient of friction. These tests should be performed prior to beginning the full production run.

Clean Up

Use NWC10 EZ Cleaner or suitable solvent.

Storage and Handling

Proper personal protection equipment and adequate ventilation are required when handling this material. Please consult MSDS for details on proper handling of this material.

This product should be stored in a sealed container away from heat, flame and should not be exposed to any direct light source. Otherwise, premature cure or gel could occur.

The product should be mixed prior to use.

Nazdar[®] stands behind the quality of this product. Nazdar[®] cannot, however, guarantee the finished results because Nazdar[®] exercises no control over individual operating conditions and production procedures. While technical information and advice on the use of this product is provided in good faith, the User bears sole responsibility for selecting the appropriate product for their end-use requirements. Users are also responsible for testing to determine that our product will perform as expected during the printed item's entire life-cycle from printing, post-print processing, and shipment to end-use. Any liability associated with the use of this product is limited to the value of the product purchased from Nazdar[®].

Nazdar - World Headquarters
8501 Hedge Lane Terrace
Shawnee, KS 66227-3290 USA
Toll Free US: 866.340.3579
Tel: +1 913 422 1888
Fax: +1 913 4222296
E-mail: NazdarOrders@nazdar.com
Technical Support E-mail:
InkAnswers@Nazdar.com

Nazdar Limited - EMEA
Barton Road, Heaton Mersey
Stockport, England SK4 3EG
Tel: +44 161 442 2111
Fax: +44 161 442 2001
UK Technical Service E-mail:
technicalservicesuk@nazdar.com

Nazdar - Asia Pacific
11 Changi North Street 1 #03-03/04
Singapore 498823
Tel: +65-63854611
Fax: +65-65433690
E-mail: aspac@nazdar.com